



CONCRETE MUST BE LEVEL FLAT AND SMOOTH

21,250 LBS (9659 KG)
UPWARD FORCE @ 45°

7500 LBS (3409 KG)
DOWNWARD FORCE
PER LEG

GROUND LEVEL

DIMENSIONS INCHES (MM)				
	A	B	C	D
20' (6.1M)	92.78 (2356.61)	238.86 (6067.04)	242.04 (6147.82)	123.78 (3144.01)
30' (9.1M)	118.35 (3006.09)	346.88 (8810.75)	349.2 (8869.68)	149.35 (3793.49)
40' (12.2M)	144 (3657.6)	454.89 (11554.21)	456.48 (11594.59)	175 (4445)

UNLESS OTHERWISE SPECIFIED:
TOLERANCE:
-
X ± 0.1
XX ± 0.01
XXX ± 0.005
CUT ANGLE = 0.5
FORMED ANGLE = 3
-
DO NOT SCALE
PRINT

THIS DRAWING CONFORMS TO
ASME 14.5M - 1994 FOR
DOCUMENTATION PRACTICES
THIRD ANGLE PROJECTION



PRODUCT SERIES	STANDARD DRAWING - IN AUTODESK INVENTOR 3D MODEL	
	NAME	DATE
DRAWN BY	RM	5/10/2016
DESIGNER	RM	5/10/2016
CHECKER		

MATERIAL	DESCRIPTION CONCRETE FOUNDATION DRAWING	PART NO.	REV
SHEET SIZE B MASS	SCALE SEE ABOVE	SHEET NO. 1 OF 1	
THICKNESS			